

## **F**702-S

# Fingerprint Access Control Terminal



Just on touch! That's all it takes for accessing control to ZK Software's F702-S biometric reader. It offers the flexibility to be installed standalone or with any third party panels that support 26-bit Wiegand. Fast, reliable performance and the affordability strengthen ZK reader's competitive edge. Each reader has the capacity to store up to 2,200 fingerprint

templates and 50,000 transactions. Enrolling users is fast and easy, Since most of our readers have a user-friendly keypad and display, enrolling users is fast and easy. All our readers are easily accessed. Together with a TCP/IP or a serial port, the readers can update and synchronize automatically.

#### **Feature**


- Equipped with durable and recognizable ZK optical sensor
- 1-touch 1-second employee recognition
- Store up to 2200 templates and 5000 transactions
- Enter PINs is not necessary
- Support 50 time zones, 5 groups and 10 unlock combinations
- Tamper-proofed switch and alarm output

- Request-to-exit and alarm contacts
- · Standalone operation without a computer
- •TCP/IP, Serial and Wiegand Interfaces
- Export real time 1-touch data to 3rd party hosted or non-hosted applications
- Indicate audio-visual signals for acceptance or rejection due to valid or invalid fingerprints
- SDK available for OEM customers and software developers


## Specifications

Fingerprint Capacity	2,200 templates
Transaction Capacity	50,000
Hardware Platform	ZEM500
Sensor	ZK Optical Sensor
Algorithm Version	ZK Finger v9.0
Communication	RS232/485, TCP/IP, USB-host
Access Control Interface for	3 <sup>rd</sup> party electric lock, door sensor, exit button, alarm, DoorBell
Standard Functions	SMS, DLST, Webserver, Workcode, Anti-passback
Optional Functions	ID, Mifare, HID, Scheduled-Bell, 9 digit user ID, Self-Service Query, Automatic Status Switch, Soap, printer
Wiegand Signal	Input & Output
Display	B & W LCD Screen
Power Supply	12V DC
Operating Temperature	0°C - 45°C
Operating Humidity	20% - 80%
Dimension(W×H×D)mm	140.5×116×43.5
Gross Weight	0.85kg

## Configuration



#### Dimensions (mm)



#### ZKTeco Inc.

ZK Mansion, Wuhe Rd, Gangtou, Bantian, Buji Town, Longgang District, Shenzhen China 518129 Tel: 86-755-8960 2345/46/47/48 E-mail: sales@zkteco.com www.zkteco.com Global Offices:

USA: + 1 732-412-6007 EU: +34 916532891 Brazil: +55 31 2515-8326 Thailand: +66-027199154

Mexico: +52-55-52928418

South Africa: +27 12 259 1047 Egypt: +201110444134 Dubai: +971 4 6091 310

India: +91 8123536788

Indonesia: +62 21 2921 8949

Vietnam: +84-0169-5813007 Philippines: +63 9084118832 Russia: +8 915 178-46-81

